


RECOMMEND P.C.B. LAYOUT



CIRCUIT: SPST  
CONTACT CONFIGURATION

- NOTES:
1. ALL DIMENSIONS IN MM
  2. GENERAL TOLERANCE:  $0.0 = \pm 0.4$   
 $0.00 = \pm 0.25$
  3. TERM. NOS. FOR REF. ONLY
  4. RATING: 50ma, @12V DC
  5. TRAVEL:  $0.30 \pm 0.15$ mm
  6. OPERATING FORCE:  $160 \pm 50$ gf
  7. CONTACT RESISTANCE: 100 milliohms Max.
  8. ELECTRICAL LIFE: 100,000 CYCLES MIN.

C		10033	REVISED & REDRAWN	11/30/98	CHKD	TITLE	SCALE	DATE	DR	DWG	REV
REV.	ECN No.	DESCRIPTION	DATE	CHKD		TL 1100 D F160 Q (Was TL 1103)	2:1	5/10/94	MM	P001100	C
<p style="text-align: center;"><b>E-SWITCH®</b></p> <p style="text-align: center;">THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSMITTED</p>											